ICETRO BY TAYLOR®

Item No. _____

ISI-301TH

Soft Serve Freezer



Single Flavor

Icetro by Taylor Single Flavor, Gravity Fed, Hopper Agitator, Heat Treatment.

Features

Offer all the popular soft serve variations from low-to non-fat ice creams or yogurt.

Heat Treatment System

Provides a daily heating and cooling cycle to safely maintain dairy products up to 28 days before a complete disassembly and cleaning is required.

Freezing Cylinder

One, 3.4 quart (3.2 liter).

Mix Hopper

One, 18.5 quart (17.5 liter), Separate hopper refrigeration (SHR) maintains mix below 41ºF (5ºC) in Auto and Standby modes.

Indicator Lights

The Mix Low and Mix Out light alerts the operator to add mix. An audible alarm may be enabled to sound when mix is low. When the Mix Out light is on, the unit shuts down automatically to prevent damage.

Electronic Controls

Microprocessor touch controls are embedded. Temperatures in the hopper or freezing cylinder are displayed at any point of operation. The microprocessor maintains a creamy consistency without dispensing soft serve for up to two hours.

Standby


During long no-use periods, the Standby feature maintains safe product temperatures in the mix hopper and freezing cylinder.

Rockton, Illinois 61072
800-255-0626
Phone 815-624-8333 Fax 815-624-8000
www.taylor-company.com
info@taylor-company.com

ISO 9001:2015
Registered Firm

C ETL LISTED US
Intertek
2002774
CONFORMS TO
UL STD.621
CERTIFIED TO CSA
STD.C22.2 #120

ETL SANITATION LISTED
Intertek
2002774
CONFORMS TO
NSF STD.6



FIGURES IN BRACKETS INDICATE MILLIMETERS / DECIMAL AND FRACTIONAL DIMENSIONS EQUAL TO (PLUS OR MINUS 1/16 INCH [1.5mm]).

Weights	lbs.	kgs.
Net	309	140
Crated	383	174

**For reference only.*

	cu. ft.	cu. m.
Volume	33.84	0.96

Dimensions	in.	mm.
Width	18.1	460
Depth	33.1	841
Height	36.2	919

**Designed to rest on a plastic pad directly on counter top.*

Electrical	Maximum Fuse Size	Minimum Circuit Ampacity	Total Ampacity	Poles (P) Wires (W)
208-230/60/1 Air	25	19	16	2P 3W

This unit may be manufactured with other electrical characteristics and may have additional regulatory agency approvals. Consult the local Taylor distributor for other electrical characteristics and agency approvals based on specific electrical and country requirements.
(For exact electrical information, approval marks, and refrigerant, always refer to the data label of the unit.)

Continuing research results in steady improvements; therefore, these specifications are subject to change without notice.

Bidding Specs

Electrical: Volt _____ Hz _____ ph _____

Neutral: ☐Yes ☐No **Cooling**: ☐Air ☐Water ☐NA

Options:_____

All options may not be available in combination with others or with all electrical or cooling configurations. Please consult your local Taylor Distributor.

Specifications

Electrical
One dedicated electrical connection is required. See the Electrical chart for the proper electrical requirements. Manufactured to be permanently connected. Consult the Taylor distributor for cord and receptacle specifications.

Beater Motor
One, 1.0 HP.

Refrigeration System
Main system, one, 3,818 BTU/Hr using R404A. The main system covers Separate Hopper Refrigeration. (BTUs may vary based on application.)

BTU/hr
3,818 BTU/Hr using R404A.

Air Cooled
Minimum 7.9 in. (201 mm) on the left side, 19.7 in. (500 mm) on the right side, and 19.7 in. (500 mm) at the rear to prevent recirculation of warm air. Minimum air clearances must be met to ensure adequate airflow for optimum performance.

Accessories
Top-Mounted Cleaning water faucet with bottom Water Inlet.

Options Available, Ordered Separately
Flavor Burst compatible.

Authorized Taylor Distributor

ROCKY MOUNTAINS DISTRIBUTING
2580 S Tejon St, Englewood, CO 80110
303-825-0171
RMDColorado.com

TAYLOR®
750 N. Blackhawk Blvd.
Rockton, Illinois 61072
www.taylor-company.com